

PROJECT NAME: \_\_\_\_\_ LOCATION: \_\_\_\_\_

ITEM: \_\_\_\_\_ MODEL: \_\_\_\_\_



## FEATURES LIST

### COUNTERTOP INDUCTION RANGE

- Durable glass top, stainless steel housing and molded plastic bottom
- Touch pad controls, 4 digit LED display, and digital timer
- 6 power levels
- Automatic empty pan safety shut-off
- Temperature settings from 150° to 450°F
- Overheat protection
- Error code alert display
- Attached 5 1/2' power cord and plug
- Non-slip feet
- 10" diameter pan maximum

### WARRANTY:

1-Year limited warranty covering manufacturer's defects in material and workmanship.



Specifications subject to change without notice

Approvals: ETL listed to UL 197 Standard

## PLAN VIEW

# countertop induction range



### SPECIFICATIONS:

|                                 |                         |
|---------------------------------|-------------------------|
| Equipment (WxDxH) .....         | 12 1/16" x 14" x 2 3/4" |
| Equipment Weight .....          | 8 lbs                   |
| Shipping Weight .....           | 9 lbs                   |
| <b>Voltage</b> .....            | <b>120</b>              |
| <b>Wattage</b> .....            | <b>1800</b>             |
| <b>Amps</b> .....               | <b>15</b>               |
| <b>Plug Configuration</b> ..... | <b>5-15P</b>            |