



eLakesideFoodservice.com/modified



QUEEN MARY BANQUET CARTS | ALUMINUM

Aluminum Banquet Carts are designed to transport your heaviest loads with ultimate assurance for banquets, catering and bussing.

- · Continuous full welded shelves for highest durability
- · Aluminum material is lightweight for easier handling under heavy loads
- · Solid aluminum shelves provide added strength
- Welded tubular handle for easy control
- · Marine edges on each shelf helps contain spills
- Extra load No-Mark® cushion tread wheels absorb impact for quieter and smoother operation
- 2 fixed and 2 swivel 8" casters guide cart in a straight line, while making turns easier
- · Full perimeter bumper protects walls and furnishings
- Model 4596 is large enough to hold three 23" (584) wide oval trays per shelf



<u>11</u>								
Freight Class: 125								
Ships in: 10 days or less	!							



	Load	# of	Shelf	nelf Shelf		Overall Size		Case Weight	Case Cube		
Model	Capacity	Shelves	Size	Clearance	W	L	Н	Lbs. (Kg)	Cu. ft. (m³)		
All Shelf Edges Down											
4567	2500 lbs.	5	27" x 64" (69 x 163)	12" (305)	29" (737	62" 1575	66" 1676)	147 (66.2)	74.4 (2.1)		
4596	2500 lbs.	5	27" x 73" (69 x 185)	12" (305)	29" (737	75" 1905	66" 1676)	180 (81.1)	90.9 (2.5)		
4565	2500 lbs.	4	27" x 64" (69 x 163)	16-1/2" (419)	29" (737	62" 1575	66" 1676)	135 (60.8)	74.7 (2.1)		

Measurements in () denote metric millimeters, unless otherwise specified. Lake-Glide® Casters: 8" (203) - 2 ea. swivel, 2 ea. fixed, No-Mark, polyethylene.

OVAL TRAY CARTS | ALUMINUM

Extra strength ledges will keep you worry-free when transporting and serving large parties and banquets.

- Extra gussets are welded in all corners prevent alignment "racking" and distortion, so your trays stay level and steady
- Four 1" continuous heliarc welds per angle guide add strength in areas vulnerable to stress for long-lasting durability
- · Models 8580 and 8582 have 3-1/4" wide standard ledges, 8585 has universal ledges to conveniently accommodate most oval tray sizes

FACTORY INSTALLED OPTIONS (MODELS 8580 & 8582):

· Corner bumpers, non-marking gray rubber, mounted to the corners of the unit's base. NOTE: This adds 2" (51) to unit's width and length.



Super strong welded corner braces prevent racking.

FACTORY INSTALLED OPTIONS (MODEL 8585):

- · Perimeter bumper, non-marking gray rubber strip attached to unit base. NOTE: This adds 2" (51) to unit's width and length.
- Vertical bumpers, non-marking 8" (152) black rubber strip attached to unit uprights. NOTE: This adds 1" (25) to the unit's width and length.



Model #8580





	Accom. Tray		# of	Ledge		Overall Size		Case Weight	Case Cube
Model	Size	Ledge Type	Ledges	Clearance	W	L	Н	Lbs. (Kg)	Cu. ft. (m³)
8580	22" x 26-7/8" (559 x 683)	Standard	10	6" (152)	24-3/4" (737	27-1/2" 1676	69" 1573)	51 (23.0)	28.4 (0.8)
8582	23-1/2" x 29" (597 x 737)	Standard	9	6" (152)	26-3/8" (670	30" 762	69" 1573)	55 (24.8)	33.7 (0.9)
8585	Accepts Most Sizes*	Universal	10	6" (152)	26-1/2" (673	30" 762	70" 1778)	99 (44.6)	33.8 (0.9)

^{*}Universal ledge holds oval tray sizes: 23-1/2" x 29" (597 x 737), 22" x 26-7/8" (559 x 683) and 20-3/4" x 25-1/2" (527 x 648). Models 8580 and 8582 have Lake-Glide stem mount casters: 5" (127) - 4 ea. swivel No-Mark, polyurethane, Model 8585 has Lake-Glide plate mount casters; 5" (127) - 4 ea, swivel No-Mark polyurethane,